

# CNMG

INSERT STYLE		DIMENSIONS				PF
ANSI	ISO	I.C.	Thickness (S)	Radius (r)	Hole Size (d)	CP4010
431	12 04 04	1/2	3/16	1/64	0.203	73004
432	12 04 08	1/2	3/16	1/32	0.203	73006

# CNMG

INSERT STYLE		DIMENSIONS				PM
ANSI	ISO	I.C.	Thickness (S)	Radius (r)	Hole Size (d)	CP4020
431	12 04 04	1/2	3/16	1/64	0.203	73104
432	12 04 08	1/2	3/16	1/32	0.203	73106
433	12 04 12	1/2	3/16	3/64	0.203	73108
542	16 06 08	5/8	1/4	1/32	0.250	73112
543	16 06 12	5/8	1/4	3/64	0.250	73114
642	19 06 08	3/4	1/4	1/32	0.313	73116
643	19 06 12	3/4	1/4	3/64	0.313	73118
644	19 06 16	3/4	1/4	1/16	0.313	73120

# CNMG

INSERT STYLE		DIMENSIONS				PR
ANSI	ISO	I.C.	Thickness (S)	Radius (r)	Hole Size (d)	CP4030
432	12 04 08	1/2	3/16	1/32	0.203	73200
433	12 04 12	1/2	3/16	3/64	0.203	73202
434	12 04 16	1/2	3/16	1/16	0.203	73204
542	16 06 08	5/8	1/4	1/32	0.250	73206
543	16 06 12	5/8	1/4	3/64	0.250	73208
643	19 06 12	3/4	1/4	3/64	0.313	73210
644	19 06 16	3/4	1/4	1/16	0.313	73212